



HANMIX

PCR

The Perfect Fit For Your Car

Product parameter
manual

Tel: +86 532 80905566
Email: info@hanmix.net
Web: www.hanmix.net





WHY HANMIX?

HANMIX is an international brand with 40 years' experience in Tyre and Tyre Accessories business. HANMIX is not only a brand name, but a way for a better life. You can find security, safety and high quality life in the HANMIX World.



HANMIX THE QUALITY

HANMIX is committed to conducting comprehensive assessments of product quality, price, ability to supply our clients locally and internationally. All HANMIX products comply with international quality standards and are respected throughout the world.

-----WWW.HANMIX.NET

Quality Control:

HANMIX provides quality and quantity inspections, and offers a warranty for products purchased.



Inspected each tyre from production to the warehouse to the markets.
Inspected each tyre by serial number, tread depth and weight.
Inspected each tyre by international laboratory standards.

HANMIX PASSENGER CAR TIRE

THE PERFECT FIT FOR YOUR CAR



MIX-TOUR



MIX-COMFORT



MIX-PLUS



MIX-SEASON



MIX-LION



MIX-GRIP



MIX-UHP



GRANDRANK HX21



GRANDRANK HX22



MIX-100



MIX-200



MIX-230



HANMIX

WWW.HANMIX.NET



MIX-TOUR

HIGH PERFORMANCE TIRE



CHARACTERS



Widened shoulder tread design increases contacting area, providing better driving stability and reliability.

Continuous straight center rib design provides optimized ground contacting area, guarantees better driving safety.

4 wide longitudinal grooves design greatly improves water drainage and driving stability on slippery roads.

Lateral "S" shaped groove ensures better wet grip.



Optimized variable pitch sequence design disperses road noise and reduces vibration, driving comfort is highly improved.

Symmetrical pattern design and small notched design on the tread increases the friction between the tire and the ground, driving comfort is significantly improved.

MIX-TOUR

Rim	Size	LI/SS	Tread Depth (mm)	Std. Rim	Section Width (mm)	Overall Diameter (mm)	Standard Pressure (Kpa/PSI)
13	175/70R13	82T	7.8	5.00B	177	576	300/44
	175/70R13	82H	7.8	5.00B	177	576	300/44
	175/65R14	82T	8.0	5J	177	584	300/44
	175/65R14	82H	8.0	5J	177	584	300/44
	175/70R14	84T	8.2	5J	177	602	300/44
	175/70R14	84H	8.2	5J	177	602	300/44
14	175/70R14	88T XL	8.2	5J	177	602	340/50
	185/60R14	82T	8.4	5 1/2J	189	578	300/44
	185/60R14	82H	8.4	5 1/2J	189	578	300/44
	185/65R14	86T	8.0	5 1/2J	189	596	300/44
	185/65R14	86H	8.0	5 1/2J	189	596	300/44
	185/70R14	88T	8.0	5 1/2J	189	616	300/44
	185/70R14	88H	8.0	5 1/2J	189	616	300/44
	195/60R14	86H	8.4	6J	201	590	300/44
	195/70R14	91T	8.0	6J	201	630	300/44
	195/70R14	91H	8.0	6J	201	630	300/44
	205/60R14	88H	7.9	6J	209	602	300/44
	185/55R15	82V	8.0	6J	194	585	300/44
	185/60R15	88H XL	8.0	5 1/2J	189	603	340/50
	185/65R15	88H	8.0	5 1/2J	189	621	300/44
15	185/65R15	92T XL	8.0	5 1/2J	189	621	340/50
	195/50R15	82V	8.0	6J	201	577	300/44
	195/55R15	85V	8.0	6J	201	595	300/44
	195/60R15	88H	8.4	6J	201	615	300/44
	195/60R15	88V	8.4	6J	201	615	300/44
	195/65R15	91H	8.0	6J	201	635	300/44
	195/65R15	91V	8.0	6J	201	635	300/44
	205/60R15	91V	8.2	6J	209	627	300/44
	205/65R15	94V	8.5	6J	209	647	300/44
	205/70R15	96T	8.2	6J	209	669	300/44
	205/70R15	96H	8.2	6J	209	669	300/44
	215/65R15	100H XL	8.2	6 1/2J	221	661	340/50
	215/70R15	98T	8.2	6 1/2J	221	683	300/44
	215/70R15	98H	8.2	6 1/2J	221	683	300/44
	235/75R15	105T	8.2	6 1/2J	235	733	300/44
	235/75R15	105S	8.2	6 1/2J	235	733	300/44
	195/60R16	89H	8.4	6J	201	640	300/44
16	205/55R16	91V	8.0	6 1/2J	214	632	300/44
	205/55R16	94W XL	8.0	6 1/2J	214	632	340/50
	205/60R16	92H	8.2	6J	209	652	300/44
	205/60R16	92V	8.2	6J	209	652	300/44
	205/60R16	96V XL	8.2	6J	209	652	340/50
	215/55R16	93V	8.2	7J	226	642	300/44
	215/60R16	95H	8.2	6 1/2J	221	664	300/44
	215/60R16	95V	8.2	6 1/2J	221	664	300/44
	215/60R16	99V XL	8.2	6 1/2J	221	664	340/50
	215/65R16	98T	8.5	6 1/2J	221	686	300/44
	215/65R16	98H	8.5	6 1/2J	221	686	300/44
	225/60R16	98H	8.5	6 1/2J	228	676	300/44
	235/60R16	100H	8.5	7J	240	688	300/44
	235/60R16	100V	8.5	7J	240	688	300/44
	235/60R16	104H XL	8.5	7J	240	688	340/50
	235/65R16	103H	8.2	7J	240	712	300/44
17	225/60R17	99T	8.2	6 1/2J	228	702	300/44
	225/60R17	99H	8.2	6 1/2J	228	702	300/44




MIX-COMFORT

HIGH PERFORMANCE TIRE




CHARACTERS



Excellent Grip Performance:
Asymmetrical pattern design ensures the grip of the tire when turning and improves the handling performance.

Optimizing the tread width of the driving surface and the high proportion of the upper and lower cambered surface improves the wet grip performance.



Low Noise and More Comfortable:
Dual pitch design with optimal pitch order can effectively reduce the noise peak.

The staggered steel sheet on tread center and semi-enclosed shoulder design reduce the tire noise.

MIX-COMFORT

Rim	Size	LI/SS	Tread Depth (mm)	Std. Rim	Section Width (mm)	Overall Diameter (mm)	Standard Pressure (Kpa/PSI)
13	155/65R13	73T	7.0	4.50B	157	532	300/44
	155/70R13	75T	7.0	4.50B	157	548	300/44
	165/65R13	77T	7.0	5.00B	170	544	300/44
	165/70R13	79T	7.0	5.00B	170	562	300/44
	165/70R13	83T XL	7.0	5.00B	170	562	340/50
	175/60R13	77T	7.0	5.00B	177	540	300/44
	185/70R13	86T	7.0	5.00B	189	590	300/44
14	155/65R14	75H	7.0	4 1/2J	157	558	300/44
	155/65R14	75T	7.0	4 1/2J	157	558	300/44
	165/60R14	75H	7.0	5J	170	554	300/44
	165/60R14	75T	7.0	5J	170	554	300/44
	165/65R14	79T	7.0	5J	170	570	300/44
	165/65R14	83T XL	7.0	5J	170	570	340/50
	165/70R14	81H	7.0	5J	170	588	300/44
	165/70R14	81T	7.0	5J	170	588	300/44
	175/65R14	82H	7.0	5J	177	584	300/44
	175/65R14	82T	7.0	5J	177	584	300/44
	185/60R14	82H	7.0	5 1/2J	189	578	300/44
	185/60R14	82T	7.0	5 1/2J	189	578	300/44
	185/65R14	86H	7.0	5 1/2J	189	596	300/44
	185/65R14	86T	7.0	5 1/2J	189	596	300/44
	185/70R14	88H	7.0	5 1/2J	189	616	300/44
	185/70R14	88T	7.0	5 1/2J	189	616	300/44
	205/70R14	95H	7.5	6J	209	644	300/44
	205/70R14	95T	7.5	6J	209	644	300/44
15	175/65R15	84H	7.5	5J	177	609	300/44
	175/65R15	84T	7.5	5J	177	609	300/44
	185/65R15	88H	7.2	5 1/2J	189	621	300/44
	185/65R15	88T	7.2	5 1/2J	189	621	300/44
	195/60R15	88H	7.5	6J	201	615	300/44
	195/60R15	88T	7.5	6J	201	615	300/44
	195/65R15	91H	7.2	6J	201	635	300/44
	195/65R15	91V	7.2	6J	201	635	300/44
	205/65R15	94V	7.5	6J	209	647	300/44
	205/65R15	94H	7.5	6J	209	647	300/44
16	205/55R16	91V	7.2	6 1/2J	214	632	300/44
	205/55R16	94V XL	7.2	6 1/2J	214	632	340/50
	215/60R16	99V XL	7.5	6 1/2J	221	664	340/50
	215/60R16	99H XL	7.5	6 1/2J	221	664	340/50





MIX-PLUS

HIGH PERFORMANCE TIRE



CHARACTERS



- 1 Deflected from the pattern design, reduce drive noise.
- 2 High tensile steel belt, lower rolling resistance, improving handling safety at the same time, more fuel-efficient, environmentally friendly.
- 3 Improved the driving stability and comfort by adopting non-jointed bead ring and reinforced bead filler.
- 4 Endless material layer, increased durability and brake so that more uniform tread ground, handling safety promotion.



Asymmetric tread and shoulder strengthening design provides good handling, ensuring driving safety.



Single-oriented Y-shaped pattern design, provide a quick line or horizontal drainage.

Wide linear gap and hole y-shaped design from the water, ensure the safety of slippery roads and driving in bad weather.

MIX-PLUS

Rim	Size	LI/SS	Tread Depth (mm)	Std. Rim	Section Width (mm)	Overall Diameter (mm)	Standard Pressure (Kpa/PSI)
13	155/65R13	73T	7.8	4.50B	157	532	300/44
	155/80R13	79T	7.8	4.50B	157	578	300/44
	165/65R13	77T	7.8	5.00B	170	544	300/44
	165/70R13	79T	7.8	5.00B	170	562	300/44
	175/70R13	82T	7.8	5.00B	177	576	300/44
14	185/70R13	86T	8.0	5.50B	189	590	300/44
	155/65R14	75T	7.8	4.50B	157	558	300/44
	165/60R14	75H	7.8	5.00B	170	554	300/44
	165/70R14	85T XL	7.8	5J	170	588	340/50
	175/65R14	82T	8.0	5J	177	584	300/44
	175/70R14	88H XL	7.8	5J	177	602	340/50
	185/65R14	86H	8.0	5 1/2J	189	596	300/44
	185/70R14	88T	8.0	5 1/2J	189	616	300/44
	195/60R14	86H	7.9	6J	201	590	300/44
15	195/65R14	89H	8.0	6J	201	610	300/44
	195/70R14	91H	8.0	6J	201	630	300/44
	185/60R15	88H XL	8.4	5 1/2J	189	603	340/50
	195/60R15	88H	7.8	6J	201	615	300/44
	195/60R15	88V	7.8	6J	201	615	300/44
	195/65R15	91H	8.0	6J	201	635	300/44
	195/65R15	95H XL	8.0	6J	201	635	340/50
16	195/65R15	91V	8.0	6J	201	635	300/44
	205/70R15	96H	8.0	6J	209	669	300/44
	215/70R15	98H	8.0	6 1/2J	221	683	300/44
	195/60R16	89H	8.0	6J	201	640	300/44
	205/55R16	91V	8.0	6 1/2J	214	632	300/44
	205/60R16	96V XL	8.0	6J	209	652	340/50
	215/60R16	99V XL	8.0	6 1/2J	221	664	340/50
	225/60R16	98H	8.5	6 1/2J	228	676	300/44





MIX-SEASON

ON-ROAD SUV TIRE



CHARACTERS



4 longitudinal grooves design guarantees the safe maneuverability on the both dry and wet road.

Superior tread design provides excellent maneuverability and grip performance under all weather conditions.

Noise is dispersed by increased numbers of pitches and the optimized angle design.



Lateral pattern grooves on shoulder part ensures the best drainage performance.

MIX-SEASON

Rim	Size	LI/SS	Tread Depth (mm)	Std. Rim	Section Width (mm)	Overall Diameter (mm)	Standard Pressure (Kpa/PSI)
15	265/70R15	112H	8.5	8J	272	753	300/44
16	215/65R16	98H	8.5	6 1/2J	221	686	300/44
	215/65R16	102 XL	8.5	6 1/2J	221	686	340/50
	215/70R16	100H	8.5	6 1/2J	221	708	300/44
	215/70R16	104H XL	8.5	6 1/2J	221	708	340/50
	225/70R16	103H	8.7	6 1/2J	228	722	300/44
	235/60R16	104V XL	8.5	7J	240	688	340/50
	235/70R16	106H	8.5	7J	240	736	300/44
	245/70R16	107H	8.5	7J	248	750	300/44
	245/70R16	107T	8.5	7J	248	750	300/44
	255/70R16	111T	8.5	7 1/2J	260	764	300/44
17	265/70R16	112T	8.5	8J	272	778	300/44
	215/60R17	96H	8.5	6 1/2J	221	690	300/44
	225/65R17	102H	8.5	6 1/2J	228	724	300/44
	235/65R17	108H XL	8.5	7J	240	738	340/50
	245/65R17	107H	8.8	7J	248	750	300/44
	245/70R17	110H	8.5	7J	248	776	300/44
	255/60R17	110H XL	8.5	7 1/2J	260	738	340/50
	255/65R17	114H XL	8.5	7 1/2J	260	764	340/50
	265/65R17	112H	8.5	8J	272	776	300/44
	265/65R17	116H XL	8.5	8J	272	776	340/50
18	275/65R17	119H XL	8.7	8J	279	790	340/50
	225/60R18	100H	8.2	6 1/2J	228	727	300/44
	235/50R18	101W XL	8.5	6 1/2J	245	693	340/50
	235/60R18	103H	8.5	7J	240	739	300/44
20	275/60R20	119H XL	8.5	8J	279	838	340/50





MIX-LION


SUV, COMMERCIAL CAR TIRE



CHARACTERS



Optimized Pattern Design:
Through 5 pitch design effectively reduces noise and improves comfort.



Excellent Drainage Performance:
4 longitudinal grooves interconnecting with the edge grooves offers better drainage performance, safely driving under rainy weather is further guaranteed consequently.



The excellent pattern design:
Small notched design on tread patterns improves the durability of the tire and the grip performance on wet ground.



"Pop-up" Design:
Stepped groove design avoids small stones embedded into tire patterns damaging the tire, better guarantees the driving stability.



- ① Jointless and high-strength nylon covering layer.
- ② High tension steel belt.
- ③ Dual carcass construction.
- ④ Jointless and high-strength bead steel wire.



WSW Size: 225/70R15

MIX-LION

Rim	Size	LI/SS	Tread Depth (mm)	Std. Rim	Section Width (mm)	Overall Diameter (mm)	Standard Pressure (Kpa/PSI)
15	215/75R15	100S	9.5	6J	216	703	300/44
	215/75R15	100H	9.5	6J	216	703	300/44
	225/70R15	100S	8.0	6 1/2J	228	697	300/44
	225/70R15(WSW)	100H	8.0	6 1/2J	228	697	300/44
	235/75R15	105S	9.5	6 1/2J	235	733	300/44
16	235/75R15	105H	9.5	6 1/2J	235	733	300/44
	215/65R16	98H	9.5	6 1/2J	221	686	300/44
	265/70R16	112S	9.5	8J	272	778	300/44
17	225/60R17	99H	9.5	6 1/2J	228	702	300/44
	225/65R17	102H	9.0	6 1/2J	228	724	300/44
	235/55R17	99H	9.5	7 1/2J	245	690	300/44
	235/55R17	99S	9.5	7 1/2J	245	690	300/44
	235/65R17	104S	9.2	7J	240	738	300/44
	235/65R17	104H	9.2	7J	240	738	300/44
	235/65R17	108H XL	9.2	7J	240	738	340/50
	245/65R17	107T	8.8	7J	248	750	300/44
	265/70R17	115T	9.0	8J	272	804	300/44
	265/70R17	115H	9.0	8J	272	804	300/44



MIX-GRIP

ULTRA HIGH PERFORMANCE TIRE



CHARACTERS



Pore-free sidewall design without bumps for nice appearance.


Four longitudinal groove and the inside open shoulder groove design, provide the excellent handling and drainage performance; and the braking distance of 100km is reduced more than 7% on wetland.

Close lateral shoulder groove can reduce air flow noise and improve the stability of outer wheels turning.



AFB silencing block design in the groove can break the natural frequency of air flow and reduce the noise.

The unique design of "water absorber" increases the absorption capacity of water on the ground and improves the driving stability of vehicles in straight lines and curves on wet slippery road.



MIX-GRIP

Rim	Tire Size	Load Index	Speed Grade	Load Range	Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Std. Rim	Standard Pressure (Kpa)
26	295/30R26	107	Y	XL	301	838	8.0	10.5J	290
24	295/35R24	110	Y	XL	301	816	8.0	10.5J	290
	295/30R24	104	Y	XL	301	788	8.0	10.5J	290
	255/30R24	97	W	XL	260	764	8.0	9.0J	290
	285/45R22	114	Y	XL	285	815	8.0	9.5J	290
22	285/40R22	110	Y	XL	290	787	8.0	10.0J	290
	285/35R22	106	Y	XL	290	759	8.0	10.0J	290
	265/40R22	106	W	XL	271	771	8.0	9.5J	290
	265/35R22	102	W	XL	271	745	8.0	9.5J	290
	245/30R22	92	W	XL	248	707	8.0	8.5J	290
	235/30R22	90	W	XL	241	701	8.0	8.5J	290
	325/30R21	108	Y	XL	331	729	8.0	11.5J	290
	285/35R21	105	Y	XL	290	733	8.0	10.0J	290
21	275/45R21	110	W	XL	273	781	8.0	9.0J	290
	265/40R21	105	W	XL	271	745	8.0	9.5J	290
	245/35R21	96	Y	XL	248	705	8.0	8.5J	290
	315/35R20	110	Y	XL	320	728	8.0	11.0J	290
20	285/50R20	116	W	XL	297	794	8.0	9.0J	290
	285/35R20	104	W	XL	290	708	8.0	10.0J	290
	285/30R20	99	W	XL	290	680	8.0	10.0J	290
	275/55R20	117	W/V	XL	284	810	8.0	8.5J	290
	275/45R20	106	W	SL	273	756	8.0	9.0J	250
	275/40R20	105	W	XL	278	703	8.0	9.5J	290
	275/35R20	102	W	XL	278	700	8.0	9.5J	290
	275/30R20	97	W	XL	278	674	8.0	9.5J	290
	265/50R20	111	W/V	XL	277	774	8.0	8.5J	290
	265/45R20	108	W	XL	266	746	8.0	9.0J	290
	265/35R20	99	W	XL	271	694	8.0	9.5J	290
	255/50R20	109	W/V	XL	265	764	8.0	8.0J	290
	255/45R20	105	W	XL	255	738	8.0	8.5J	290
	255/40R20	101	W	XL	260	712	8.0	9.0J	290
	255/35R20	97	W	XL	260	686	8.0	9.0J	290
	245/50R20	105	W/V	XL	253	754	8.0	7.5J	290
	245/45R20	103	W	XL	243	728	8.0	8.0J	290
	245/40R20	99	W	XL	248	704	8.0	8.5J	290
	245/35R20	95	W	XL	248	680	8.0	8.5J	290
	245/30R20	90	W	XL	248	656	8.0	8.5J	290
	235/35R20	92	W	XL	241	672	8.0	8.5J	290
	235/30R20	88	W	XL	241	650	8.0	8.5J	290
	225/35R20	90	W	XL	230	666	8.0	8.0J	290
	225/30R20	85	W	XL	230	644	8.0	8.0J	290
19	285/45R19	111	Y	XL	285	739	8.0	9.5J	290
	285/40R19	107	W	XL	290	711	8.0	10.0J	290
	285/35R19	103	W	XL	290	683	8.0	10.0J	290
	275/55R19	111	W	SL	284	785	8.0	8.5J	250
	275/45R19	108	W	XL	273	731	8.0	9.0J	290

MIX-GRIP

Rim	Tire Size	Load Index	Speed Grade	Load Range	Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Std. Rim	Standard Pressure (Kpa)
19	275/40R19	105	W	XL	278	703	8.0	9.5J	290
	275/35R19	100	W	XL	278	675	8.0	9.5J	290
	265/50R19	110	W/V	XL	277	749	8.0	8.5J	290
	265/35R19	98	W	XL	271	669	8.0	9.5J	290
	265/30R19	93	W	XL	271	643	8.0	9.5J	290
	255/55R19	111	W/V	XL	265	763	8.0	8.0J	290
	255/50R19	107	W	XL	265	739	8.0	8.0J	290
	255/45R19	104	W	XL	255	713	8.0	8.5J	290
	255/40R19	100	W	XL	260	687	8.0	9.0J	290
	255/35R19	96	W	XL	260	661	8.0	9.0J	290
	255/30R19	91	Y	XL	260	637	8.0	9.0J	290
	245/55R19	103	V	SL	253	753	8.0	7.5J	250
	245/45R19	102	W	XL	243	703	8.0	8.0J	290
	245/40R19	98	W	XL	248	679	8.0	8.5J	290
	245/35R19	93	W	XL	248	655	8.0	8.5J	290
	235/55R19	105	W	XL	245	741	8.0	7.5J	290
	235/50R19	103	W	XL	245	719	8.0	7.5J	290
	235/40R19	96	W	XL	241	671	8.0	8.5J	290
	235/35R19	91	W	XL	241	647	8.0	8.5J	290
	225/45R19	96	W	XL	225	685	8.0	7.5J	290
	225/40R19	93	W	XL	230	663	8.0	8.0J	290
	225/35R19	88	W	XL	230	641	8.0	8.0J	290
	215/35R19	85	Y	XL	218	633	8.0	7.5J	290
18	275/40R18	103	W	XL	278	677	8.0	9.5J	290
	265/40R18	101	W	XL	271	669	8.0	9.5J	290
	265/35R18	97	W	XL	271	643	8.0	9.5J	290
	255/55R18	105	V	SL	265	737	8.0	8.0J	250
	255/45R18	103	W	XL	255	687	8.0	8.5J	290
	255/40R18	99	W	XL	260	661	8.0	9.0J	290
	255/35R18	94	W	XL	260	635	8.0	9.0J	290
	245/45R18	100	W	XL	243	677	8.0	8.0J	290
	245/40R18	97	W	XL	248	653	8.0	8.5J	290
	235/55R18	104	W/V	XL	245	715	8.0	7.5J	290
	235/50R18	101	W	XL	245	693	8.0	7.5J	290
	235/45R18	98	W	XL	236	669	8.0	8.0J	290
	235/40R18	95	W	XL	241	645	8.0	8.5J	290
	225/55R18	102	W/V	XL	233	705	8.0	7.0J	290
	225/50R18	99	W/V	XL	233	683	8.0	7.0J	290
	225/45R18	95	W	XL	225	659	8.0	7.5J	290
	225/40R18	92	W	XL	230	637	8.0	8.0J	290
	215/45R18	93	W	XL	213	651	8.0	7.0J	290
	215/40R18	89	W	XL	218	629	8.0	7.5J	290
	215/35R18	84	W	XL	218	607	8.0	7.5J	290
17	245/45R17	99	W	XL	243	652	8.0	8.0J	290
	245/40R17	95	W	XL	248	628	8.0	8.5J	290
	235/55R17	103	W/V	XL	245	690	8.0	7.5J	290

MIX-GRIP

Rim	Tire Size	Load Index	Speed Grade	Load Range	Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Std. Rim	Standard Pressure (Kpa)
17	235/50R17	100	W/V	XL	245	668	8.0	7.5J	290
	235/45R17	97	W	XL	236	644	8.0	8.0J	290
	225/55R17	97	W	SL	233	680	8.0	7.0J	250
	225/50R17	98	W	XL	233	658	8.0	7.0J	290
	225/45R17	94	W	XL	225	634	8.0	7.5J	290
	215/55R17	94	V	SL	226	668	8.0	7.0J	250
	215/50R17	95	W	XL	226	648	8.0	7.0J	290
	215/45R17	91	W	XL	213	626	8.0	7.0J	290
	215/40R17	87	W	XL	218	604	8.0	7.5J	290
	205/55R17	95	W/V	XL	214	658	8.0	6.5J	290
	205/50R17	89	V	SL	214	638	8.0	6.5J	250
	205/45R17	88	W	XL	206	616	8.0	7.0J	290
	205/40R17	84	W	XL	212	596	8.0	7.5J	290
	225/55R16	99	W/V	XL	233	654	8.0	7.0J	290
16	225/50R16	96	W/V	XL	233	632	8.0	7.0J	290
	215/55R16	97	V	XL	226	642	8.0	7.0J	290
	205/55R16	91	V	SL	214	632	8.0	6.5J	250
	205/45R16	87	W	XL	206	590	8.0	7.0J	290





MIX-UHP

ULTRA HIGH PERFORMANCE TIRE



CHARACTERS



Big pattern design:
Greatly improving cornering stability at high speed.

Straight lined central rib design:
Maneuverability is highly improved.

Four main rib design:
Better avoiding slippery.

Asymmetric tread design:
Offers better sporting performance.



Best footprint shape simulated by computer offers excellent braking performance.



- 1 Pitched pattern design reduces driving noise.
- 2 Special compound improves driving and gripping performance while maintaining excellent heat-resistant and wear-resistant ability.
- 3 Rim protection bar to protect the rim from any external damage.
- 4 All-new jointless protection layer improves the durability and braking performance, offers even landing and safe driving.
- 5 High strength steel belt reduces rolling resistance. To be more fuel saving and environmental while maintaining the driving safety.

MIX-UHP

Rim	Size	LI/SS	Tread Depth (mm)	Std. Rim	Section Width (mm)	Overall Diameter (mm)	Standard Pressure (Kpa/PSI)
15	195/50R15	82H	8.0	6J	201	577	300/44
16	195/45R16	80V	8.0	6 1/2J	195	582	300/44
	195/45R16	84V XL	8.0	6 1/2J	195	582	340/50
	195/50R16	84V	8.0	6J	201	602	300/44
	195/50R16	88V XL	8.0	6J	201	602	340/50
	195/55R16	87V	8.0	6J	201	620	300/44
	195/55R16	91V XL	8.0	6J	201	620	340/50
	205/50ZR16	87W	8.2	6 1/2J	214	612	300/44
	205/50ZR16	91W XL	8.2	6 1/2J	214	612	340/50
	205/55R16	91V	8.4	6 1/2J	214	632	300/44
	205/55ZR16	94W XL	8.4	6 1/2J	214	632	340/50
	215/55ZR16	93W	8.2	7J	226	642	300/44
	215/55ZR16	97W XL	8.2	7J	226	642	340/50
	225/50ZR16	92W	8.4	7J	233	632	300/44
	225/50ZR16	96W XL	8.4	7J	233	632	340/50
	225/55ZR16	95W	8.2	7J	233	654	300/44
17	225/55ZR16	99W XL	8.2	7J	233	654	340/50
	205/40ZR17	80W	8.2	7 1/2J	212	596	300/44
	205/40ZR17	80Y	8.2	7 1/2J	212	596	300/44
	205/40ZR17	84W XL	8.2	7 1/2J	212	596	340/50
	205/40ZR17	84Y XL	8.2	7 1/2J	212	596	340/50
	205/45ZR17	84W	8.0	7J	206	616	300/44
	205/45ZR17	84Y	8.0	7J	206	616	300/44
	205/45ZR17	88W XL	8.0	7J	206	616	340/50
	205/45ZR17	88Y XL	8.0	7J	206	616	340/50
	205/50ZR17	89W	8.7	6 1/2J	214	638	300/44
	205/50ZR17	93W XL	8.7	6 1/2J	214	638	340/50
	205/50ZR17	93Y XL	8.7	6 1/2J	214	638	340/50
	215/40ZR17	87W XL	8.0	7 1/2J	218	604	340/50
	215/40ZR17	87Y XL	8.0	7 1/2J	218	604	340/50
	215/45ZR17	87W	8.0	7J	213	626	300/44
	215/45ZR17	91W XL	8.0	7J	213	626	340/50
	215/45ZR17	91Y XL	8.0	7J	213	626	340/50
	215/50ZR17	95W XL	8.0	7J	226	648	340/50
	215/50ZR17	95Y XL	8.0	7J	226	648	340/50
	215/55ZR17	94W	8.2	7J	226	668	300/44
	215/55ZR17	98W XL	8.2	7J	226	668	340/50
	215/55ZR17	98Y XL	8.2	7J	226	668	340/50
	225/45ZR17	91W	8.2	7 1/2J	225	634	300/44
	225/45ZR17	94W XL	8.2	7 1/2J	225	634	340/50
	225/45ZR17	94Y XL	8.2	7 1/2J	225	634	340/50
	225/50ZR17	94W	8.7	7J	233	658	300/44
	225/50ZR17	98W XL	8.7	7J	233	658	340/50
	225/55ZR17	97W	8.4	7J	233	680	300/44
	225/55ZR17	101W XL	8.4	7J	233	680	340/50

MIX-UHP

Rim	Size	LI/SS	Tread Depth (mm)	Std. Rim	Section Width (mm)	Overall Diameter (mm)	Standard Pressure (Kpa/PSI)
17	225/55ZR17	101Y XL	8.4	7J	233	680	340/50
	235/45ZR17	94W	8.2	8J	236	644	300/44
	235/45ZR17	97Y XL	8.2	8J	236	644	340/50
	235/55ZR17	103W XL	8.0	7 1/2J	245	690	340/50
	235/55ZR17	103Y XL	8.0	7 1/2J	245	690	340/50
	245/40ZR17	95W XL	8.0	8 1/2J	248	628	340/50
	245/45ZR17	95W	8.2	8J	243	652	300/44
	245/45ZR17	99W XL	8.2	8J	243	652	340/50
18	245/45ZR17	99Y XL	8.2	8J	243	652	340/50
	215/35ZR18	84W XL	8.0	7 1/2J	218	607	340/50
	215/35ZR18	84Y XL	8.0	7 1/2J	218	607	340/50
	215/40ZR18	85W	8.0	7 1/2J	218	629	300/44
	215/40ZR18	89W XL	8.0	7 1/2J	218	629	340/50
	215/40ZR18	89Y XL	8.0	7 1/2J	218	629	340/50
	215/55ZR18	95W	8.2	7J	226	693	300/44
	225/40ZR18	88W	8.2	8J	230	637	300/44
	225/40ZR18	92W XL	8.2	8J	230	637	340/50
	225/40ZR18	92Y XL	8.2	8J	230	637	340/50
	225/45ZR18	91W	8.2	7 1/2J	225	659	300/44
	225/45ZR18	95W XL	8.2	7 1/2J	225	659	340/50
	225/45ZR18	95Y XL	8.2	7 1/2J	225	659	340/50
	235/40ZR18	95W XL	8.2	8 1/2J	241	645	340/50
	235/45ZR18	94W	8.2	8J	236	669	300/44
	235/45ZR18	98W XL	8.2	8J	236	669	340/50
	235/45ZR18	98Y XL	8.2	8J	236	669	340/50
	235/55ZR18	104W XL	8.0	7 1/2J	245	715	340/50
	245/40ZR18	97W XL	8.0	8 1/2J	248	653	340/50
	245/40ZR18	97Y XL	8.0	8 1/2J	248	653	340/50
	245/45ZR18	96W	8.2	8J	243	677	300/44
	245/45ZR18	100W XL	8.2	8J	243	677	340/50
	245/45ZR18	100Y XL	8.2	8J	243	677	340/50
	255/35ZR18	94W XL	8.0	9J	260	635	340/50
	255/45ZR18	99W	8.0	8 1/2J	255	687	300/44
	255/45ZR18	103W XL	8.0	8 1/2J	255	687	340/50
	255/55R18	105V	8.0	8J	265	737	300/44
	255/55R18	109V XL	8.0	8J	265	737	340/50
19	225/40ZR19	93Y XL	8.0	8J	230	663	340/50
	225/45ZR19	96Y XL	8.0	7 1/2J	225	685	340/50
	235/35ZR19	91W XL	8.2	8 1/2J	241	647	340/50
	235/40ZR19	92W	8.0	8 1/2J	241	671	300/44
	235/40ZR19	96W XL	8.0	8 1/2J	241	671	340/50
	235/50ZR19	103W XL	8.0	7 1/2J	245	719	340/50
	235/55ZR19	105W XL	8.0	7 1/2J	245	741	340/50
	245/35ZR19	89W	8.2	8 1/2J	248	655	300/44
	245/35ZR19	93W XL	8.2	8 1/2J	248	655	340/50
	245/40ZR19	98W XL	8.0	8 1/2J	248	679	340/50

MIX-UHP

Rim	Size	LI/SS	Tread Depth (mm)	Std. Rim	Section Width (mm)	Overall Diameter (mm)	Standard Pressure (Kpa/PSI)
19	245/45ZR19	102W XL	8.2	8J	243	703	340/50
	245/55ZR19	103W	8.0	7 1/2J	253	753	300/44
	255/35ZR19	92W	8.0	9J	260	661	300/44
	255/35ZR19	96W XL	8.0	9J	260	661	340/50
	255/40ZR19	100Y XL	8.0	9J	260	687	340/50
	255/45ZR19	104W XL	8.0	8 1/2J	255	713	340/50
	255/50R19	103V	8.0	8J	265	739	300/44
	255/50R19	107V XL	8.0	8J	265	739	340/50
	255/55ZR19	107W	8.0	8J	265	763	300/44
	255/55ZR19	111W XL	8.0	8J	265	763	340/50
20	255/55ZR19	111Y XL	8.0	8J	265	763	340/50
	265/35ZR19	98Y XL	8.0	9 1/2J	271	669	340/50
	265/50ZR19	106W	8.2	8 1/2J	277	749	300/44
	265/50ZR19	110W XL	8.2	8 1/2J	277	749	340/50
	265/50ZR19	110Y XL	8.2	8 1/2J	277	749	340/50
	275/40ZR19	101W	8.2	9 1/2J	278	703	300/44
	275/40ZR19	105W XL	8.2	9 1/2J	278	703	340/50
	275/40ZR19	105Y XL	8.2	9 1/2J	278	703	340/50
	275/45ZR19	104W	8.0	9J	273	731	300/44
	275/45ZR19	108W XL	8.0	9J	273	731	340/50
	275/45ZR19	108Y XL	8.0	9J	273	731	340/50
	285/45R19	111V XL	8.0	9 1/2J	285	739	340/50
	225/30ZR20	85W XL	7.8	8J	230	644	340/50
	225/35ZR20	90W XL	8.2	8J	230	666	340/50
	235/55ZR20	105W XL	8.0	7 1/2J	245	766	340/50
	245/35ZR20	95W XL	8.0	8 1/2J	248	680	340/50
	255/35ZR20	93W	8.2	9J	260	686	300/44
	255/35ZR20	97W XL	8.2	9J	260	686	340/50
	255/50R20	104 V	8.0	8J	265	764	300/44
	265/50R20	111V XL	8.0	8 1/2J	277	774	340/50
	275/40ZR20	106W XL	8.2	9 1/2J	278	728	340/50
	275/40ZR20	106Y XL	8.2	9 1/2J	278	728	340/50
	275/45ZR20	106W	8.5	9J	273	756	300/44
	275/45ZR20	110W XL	8.5	9J	273	756	340/50
	275/45ZR20	110Y XL	8.5	9J	273	756	340/50
	275/55R20	113V	8.0	8 1/2J	284	810	300/44
	315/35ZR20	106W	8.8	11J	320	728	300/44
	315/35ZR20	110W XL	8.8	11J	320	728	340/50
	315/35ZR20	110Y XL	8.8	11J	320	728	340/50
21	265/40ZR21	105Y XL	8.0	9 1/2J	271	745	340/50
	275/45R21	110W XL	8.0	9J	273	781	340/50
22	245/30ZR22	92W XL	8.0	8 1/2J	248	707	340/50
	265/35ZR22	102W XL	8.0	9 1/2J	271	745	340/50
	285/45ZR22	114W XL	8.0	9 1/2J	285	815	340/50
	285/45ZR22	114Y XL	8.0	9 1/2J	285	815	340/50
24	255/30ZR24	97W XL	8.0	9J	260	764	340/50



GRANDRANK HX21

ALL SEASON SUV TIRE



CHARACTERS




Four wide grooves design provide effective drainage and sufficient wet safety performance.

The compact shoulder design provide excellent handling performance with low noise.

Design of central rib with sipes promotes the rigidity, help to balance high-speed performance and grip performance on wet land.

Multiple blade groove pattern provide excellent grip and handling performance on wet land.



Size	LI/SS	Max. Load (kg)	Section Width (mm)	Overall Diameter (mm)	Standard Pressure (Kpa/PSI)
265/70R17	115T	1215	272	798	300
265/60R18	110H	1060	272	767	300
285/50R20	116V XL	1250	297	785	340



GRANDRANK HX22

ALL TERRAIN SUV TIRE



CHARACTERS




Solid staggered central rib design ensures straight-line driving stability and safety.

Enhance the block rigidity, endurance, weight-carrying ability and steering qualities during driving.

Promote the grip performance on wet and dry land, enhance the tractive performance.

Prevent stone nipped, enhance the ability to get rid of the stone.



Size	LI/SS	Max. Load (kg)	Max. Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)
265/70R16	112T	1120	300	772	272
275/70R16	114T	1180	300	783	279
265/65R17	112T	1120	300	767	272
285/65R17	116H	1250	300	799	292
285/60R18	120H XL	1400	340	791	292

LIGHT TRUCK RADIAL TIRE



MIX-100

LIGHT TRUCK RADIAL TIRE

SIZE	PR	STD RIM	LOAD INDEX/ SPEED RATING	MAX LOAD (KG)	PRESSURE (KPA)	TIRE DIMENSION (MM)	
						SW	OD
195R14C	8PR	5.5J	106/104 Q	925	450	196	668
195R15C	8PR	6J	106/104 Q	950	450	196	693



MIX-200

LIGHT TRUCK RADIAL TIRE

SIZE	PR	STD RIM	LOAD INDEX/ SPEED RATING	MAX LOAD (KG/LBS)		INFLATED PRESSURE (KPA/PSI)		TIRE DIMENSION (MM)	
				SINGLE	DUAL	SINGLE	DUAL	SW	OD
700R16C	12	5.50F	115/110 N	1150/2535	1120/2469	515/74	515/74	200	775
750R16C	14	6.00G	122/118 L	1405/3295	1315/2899	740/107	740/107	215	805



MIX-230

LIGHT TRUCK RADIAL TIRE

SIZE	PR	STD RIM	TUBE	SPEED SYMBOL	LOAD INDEX	MAX LOAD (KG)		INFLATED PRESSURE (KPA)		TIRE DIMENSION (MM)	
						SINGLE	DUAL	SINGLE	DUAL	SW	OD
205/70R15C	8	6J	TL	S	106/104	950	900	450	450	209	669