



HANMIX INTERNATIONAL CO., LTD
WWW.HANMIX.NET INFO@HANMIX.NET



HANMIX



FOR A BETTER LIFE

HANMIX is not only a brand name, but a way

FOR A BETTER LIFE

You can find ultimate safety and high quality living
in the HANMIX World.

WHY HANMIX



40 YEARS OF EXPERTISE

Our management brings four decades of experience in the tire and accessories industry, ensuring reliable and knowledgeable support.

COMPREHENSIVE PRODUCT RANGE

We supply a full line of tires – from bicycles to trucks, OTR, agricultural, industrial, and solid tires – along with essential accessories.

QUALITY BUILT ON TRUST

We deliver reliable, robust, and durable products, Certificate by DOT, ECE, ISO, GCC, SASO, etc. We strictly control our quality from raw material sourcing to finished product inspection.

DEDICATED SERVICE & SUPPORT

We partner with our clients, offering tailored marketing support, strong after-sales service, and customized solutions to help you succeed in your market.

—————> PRODUCT PARAMETER MANUAL

OFF-THE-ROAD RADIAL TYRE



01

WWW.HANMIX.NET

(G2) RR-444



★ Suitable for grader with a stable contour.

★ Unique pattern design offers excellent traction and grip.

SIZE	STAR LEVEL	TYPE	CODE	STD RIM	TREAD DEPTH (MM)	LOAD INDEX	LOAD&PRESSURE (KG/KPA)	DIMENSION (MM)	
							40KM/H	SW	OD
14.00R24	★★	TL	G2	8.00TG	26	153A8	3650/375	360	1350
16.00R24	★★	TL	G2	10.00VA	28	161A8	4625/375	425	1460



RR-311 (E2)



★ Exceptional operator comfort.

★ Excellent traction on all surfaces. ★ High-speed capabilities.

★ Primarily designed for high speed long haul application.

SIZE	STAR LEVEL	TYPE	CODE	STD RIM	TREAD DEPTH (MM)	LOAD INDEX	LOAD&PRESSURE (KG/KPA)		DIMENSION (MM)	
							70KM/H	80KM/H	SW	OD
14.00R24	★★★★	TL	E2	10.00W	23	170E	6000/900		375	1368
(385/95R24)	★★★★	TL	E2	10.00W	23	170F		6000/900	375	1368
14.00R25	★★★★	TL	E2	10.00/1.5	23	170E	6000/900		375	1368
(385/95R25)	★★★★	TL	E2	10.00/1.5	23	170F		6000/900	375	1368
16.00R25	★★★★	TL	E2	11.25/2.0	25	177E	7300/900		432	1493
(445/95R25)	★★★★	TL	E2	11.25/2.0	25	177F		6700/900	432	1493

(E2) RR-312



★ Mobile crane tyre, designed for on-off highway application.

★ Offers superior durability and cool running at high speed.

★ New generation of tread design optimizes tread wear and minimizes fuel consumption.

SIZE	STAR LEVEL	TYPE	CODE	STD RIM	TREAD DEPTH (MM)	LOAD INDEX	LOAD&PRESSURE (KG/KPA)		DIMENSION (MM)	
							70KM/H		SW	OD
18,00R25 (505/95R25)	★★★	TL	E2	13.00/2.5	30	186E	9500/900		498	1615



RR-313 (E2)



★ High speed capabilities.

- ★ Exceptional casing durability.
- ★ Excellent traction on all conditions both on and off highway.
- ★ The tread design improves operator comfort by reducing road noise and delivering precise handling response.

SIZE	STAR LEVEL	TYPE	CODE	STD RIM	TREAD DEPTH (MM)	LOAD INDEX	LOAD&PRESSURE (KG/KPA)		DIMENSION (MM)	
							70KM/H	80KM/H	SW	OD
16.00R25	★★★	TL	E2	11.25/2.0	23	177E	7300/900		432	1493
(445/95R25)	★★★	TL	E2	11.25/2.0	23	174F		6700/900	432	1493

(E2) RR-314



- ★ High speed capabilities.
- ★ Excellent traction on all conditions both on and off highway.
- ★ Exceptional casing durability.
- ★ The tread design improves operator comfort by reducing road noise and delivering precise handling response.

SIZE	STAR LEVEL	TYPE	CODE	STD RIM	TREAD DEPTH (MM)	LOAD INDEX	LOAD&PRESSURE (KG/KPA)		DIMENSION (MM)	
							70KM/H	80KM/H	SW	OD
385/95R25	★★★	TT/TL	E2	10.00/2.0	23	170E	6000/900		375	1368
	★★★	TT/TL	E2	10.00/2.0	23	170F	6000/900		375	1368



RR-855 (G3/L3)



Loader



Grader

★ Multiple groove edges offer superior traction on all surfaces.

- ★ Specially placed blades for optimized ice and snow traction.
- ★ Unique groove shape for optimized self-cleaning in all conditions.
- ★ Wide-base construction for high flotation, improved stability and reduced ground pressure.
- ★ Flexible block elements for minimized stone retention.

SIZE	STAR LEVEL	TYPE	CODE	STD RIM	TREAD DEPTH (MM)	LOAD INDEX	LOAD&PRESSURE (KG/KPA)		DIMENSION (MM)	
							40KM/H	10KM/H	SW	OD
17.5R25	★★	TL	G3/L3	14.00/1.5	28	153A8	3650/300		445	1348
	★★	TL	G3/L3	14.00/1.5	28	182A2	8500/650		445	1348
20.5R25	★★	TL	G3/L3	17.00/2.0	31	161A8	4625/300		521	1493
	★★	TL	G3/L3	17.00/2.0	31	193A2	11500/650		521	1493

(E3/L3) RR-111



- ★ Excellent traction.
- ★ Ensures a very comfortable ride due to its superb stability.
- ★ The inner liner with specially designed compound helps prevent air leakage.
- ★ Versatile tread pattern designed for loaders, dozer and other equipment used in construction, stockpile and truck-loading applications.

SIZE	STAR LEVEL	TYPE	CODE	STD RIM	TREAD DEPTH (MM)	LOAD INDEX	LOAD&PRESSURE (KG/KPA)		DIMENSION (MM)	
							50KM/H	10KM/H	SW	OD
17.5R25	★★	TL	E3/L3	14.00/1.5	28	167B/182A2	5450/525	8500/650	445	1348
20.5R25	★★	TL	E3/L3	17.00/2.0	30	177B/193A2	7300/525	11500/650	521	1493
23.5R25	★★	TL	E3/L3	19.5/2.5	31.5	185B/201A2	9250/450	14500/575	597	1617
23.5R25	★★	TL	E3/L3A	19.5/2.5	41	185B/201A2	9250/525	14500/650	597	1617
26.5R25	★★	TL	E3/L3	22.00/3.0	36	193B/209A2	11500/525	18500/650	673	1750
29.5R25	★★	TL	E3/L3	25.00/3.5	43	200B/216A2	14000/525	22400/650	749	1874
29.5R29	★★	TL	E3/L3	25.00/3.5	43	202B/218A2	15000/525	23600/650	749	1975



RR-114 (E3/L3)



Articulated
Dumpers

Dozer

Loader

Grader

★ Non-directional traction and standard tread depth pattern design.

★ Excellent performance supported with low heating-up compound.

★ Primarily designed for mining, off the road and muddy surfaces

SIZE	STAR LEVEL	TYPE	CODE	STD RIM	TREAD DEPTH (MM)	LOAD INDEX	LOAD&PRESSURE (KG/KPA)		DIMENSION (MM)	
							50KM/H	10KM/H	SW	OD
26.5R25	★★	TL	E3/L3	22.00/3.0	38.5	193B/209A2	11500/525	18500/650	673	1750
29.5R25	★★	TL	E3/L3	25.00/3.5	43	200B/216A2	14000/525	22400/650	749	1874

(E3/L3, G3) RR-117



★ Mainly suitable for grader, can be also used for loader.

★ Unique pattern design with good traction performance on muddy, soft and slippery road conditions.

★ Improve the self-cleaning, traffic ability and operating stability.

SIZE	STAR LEVEL	TYPE	STD RIM	TREAD DEPTH (MM)	LOAD INDEX	LOAD&PRESSURE (KG/KPA)		DIMENSION (MM)	
						50KM/H	10KM/H	SW	OD
23.5R25	★★	TT/TL	19.50/2.5	32	185B/201A2	9250/525	14500/650	597	1617



RR-118 (E3)



Rigid Dumpers

★ Transverse pattern and oblique shallow groove design.

★ Increase the anti-skidding performance in muddy condition and provide with strong grip and traction.

SIZE	STAR LEVEL	TYPE	CODE	STD RIM	TREAD DEPTH (MM)	LOAD INDEX	LOAD&PRESSURE (KG/KPA)		DIMENSION (MM)	
							50KM/H	10KM/H	SW	OD
14.00R24	★★★	TT	E3	10.00W	30	170B/188A2	6050/800	10000/1000	375	1368
14.00R25	★★★	TT	E3	10.00/2.0	28	170B/188A2	6050/800	10000/1000	375	1368

(E3) RR-119



Rigid Dumpers



- ★ Extra wide tranverse pattern.
- ★ With excellent traction performance.
- ★ Outstanding stability and long service life.

SIZE	STAR LEVEL	TYPE	CODE	STD RIM	TREAD DEPTH (MM)	LOAD INDEX	LOAD&PRESSURE (KG/KPA)		DIMENSION (MM)	
							50KM/H	10KM/H	SW	OD
14.00R24	★★★	TT	E3	10.00W	30	170B/188A2	6050/800	10000/1000	375	1368
14.00R25	★★★	TT	E3	10.00/2.0	30	170B/188A2	6050/800	10000/1000	375	1368



RR-211 (E4)



Rigid
Dumpers

- ★ Low rolling resistance and fuel economy.
- ★ Non-directional deep tread pattern designed for muddy and soft surfaces.
- ★ Great traction and floatation, operation comfort and less vehicle damage.
- ★ Superior long tread life and excellent puncture resistance.

SIZE	STAR LEVEL	TYPE	CODE	STD RIM	TREAD DEPTH (MM)	LOAD INDEX	LOAD&PRESSURE (KG/KPA)		DIMENSION (MM)	
							50KM/H		SW	OD
12.00R24	★★★	TT	E4	8.5	31.5	164/162F	5000/900 (single) 4750/900 (dual)		315	1245
18.00R33	★★	TL	E4	13.00/2.5	54	191B/209A2	10900/700		500	1875
21.00R33	★★	TT/TL	E4	15.00/3.0	54	200B	14000/650		570	1955
24.00R35	★★	TL	E4	17.00/3.5	63	209B/227A2	18500/700		655	2175
	★★★	TL	E4	17.00/3.5	63	214B	21200/900		655	2175

(E3/L3, E4/L4) RR-112



★ Special pattern design, with elegant formal expressions.

★ With excellent traction and buoyancy performance.

★ Outstanding stability and operating comfort, with large pattern plate and long service life.

SIZE	STAR LEVEL	TYPE	CODE	STD RIM	TREAD DEPTH (MM)	LOAD INDEX	LOAD&PRESSURE (KG/KPA)		DIMENSION (MM)	
							50KM/H	10KM/H	SW	OD
13.00R25	★★★	TT	E3	8.50/1.3 10.00/1.5	28	163/B	4875/700(GB)		350	1300
14.00R24	★★★	TT/TL	E3	10.00W	30	170B	6050/800	10000/1000	375	1368
14.00R25	★★★	TT/TL	E3	10.00/1.5 10.00/2.0	30	170B	6050/800	10000/1000	375	1368
14.00R25	★★★	TT/TL	E4	10.00/1.5 10.00/2.0	36	170B	6050/800	10000/1000	375	1368
16.00R25	★★★	TT	E3	11.25/2.0	28	182B/196A2	8500/900	12500/1000	432	1493
	★★★	TT/TL	E4	11.25/2.0	45	182B/196A2	8500/900	12500/1000	432	1548

RR-112

SIZE	STAR LEVEL	TYPE	CODE	STD RIM	TREAD DEPTH (MM)	LOAD INDEX	LOAD&PRESSURE (KG/KPA)		DIMENSION (MM)	
							50KM/H	10KM/H	SW	OD
17.5R25	★★	TL	L3	14.00/1.5	26.5	167B/182A2	5450/525	8500/650	445	1348
	★★	TL	E3/L3	14.00/1.5	26.5	167B/182A2	5450/525	8500/650	445	1348
	★★	TL	E4/L4	14.00/1.5	37	167B/182A2	5450/525	8500/650	445	1348
18.00R25	★★	TT/TL	E4	13.00/2.5	47	185B	9250/700		498	1673
20.5R25	★★	TL	L3	17.00/2.0	28.5	177B/193A2	7300/525	11500/650	521	1493
	★★	TL	E3/L3	17.00/2.0	28.5	177B/193A2	7300/525	11500/650	521	1493
	★★	TL	E4/L4	17.00/2.0	45	177B/193A2	7300/525	11500/650	521	1493
23.5R25	★★	TL	L3	19.5/2.5	32	185B/201A2	9250/525	14500/650	597	1617
	★★	TL	E3/L3	19.5/2.5	32	185B/201A2	9250/525	14500/650	597	1617
	★★	TL	E4/L4	19.5/2.5	48	185B/201A2	9250/525	14500/650	597	1617
26.5R25	★★	TL	L3	22.00/3.0	35	209A2/193B	11500/525	18500/650	673	1750
	★★	TL	E3/L3	22.00/3.0	35	209A2/193B	11500/525	18500/650	673	1750
	★★	TL	E4/L4	22.00/3.0	54	209A2/193B	11500/525	18500/650	673	1750
29.5R25	★★	TL	E4/L4	25.00/3.5	57	200B/216A2	14000/525	22400/650	749	1874
33.25R29	★★	TL	E3/L3	27.00/3.0	46	225A2/209B	18500/525	29000/650	845	2090
650/65R25	★★	TL	L3	19.5/2.5	38	193A2		11500/475	650	1500
	★★	TL	E3	19.5/2.5	38	180B	8000/425		650	1500
750/65R25	★★	TL	L3	24.00/3.0	43	202A2		15000/475	750	1610
	★★	TL	E3	24.00/3.0	43	190B	10600/425		750	1610

(E4, L5) RR-115



- ★ Super sidewall cut resistance.
- ★ Good self-cleaning with groove stone ejector.
- ★ Deep tread particularly suitable for loaders and dump trucks operation in quarry or mining.
- ★ Unique non-directional traction pattern ensures optimum traction and prolongs tread life.

SIZE	STAR LEVEL	TYPE	CODE	STD RIM	TREAD DEPTH (MM)	LOAD INDEX	LOAD&PRESSURE (KG/KPA)		DIMENSION (MM)	
							50KM/H	10KM/H	SW	OD
20.5R25	★★	TL	L5	17.00/2.0	68	193A2		11500/650	521	1548
23.5R25	★★	TL	L5	19.50/2.5	76	201A2		14500/650	597	1673
26.5R25	★★	TL	L5	22.00/3.0	86	209A2		18500/650	673	1798
35/65R33	★★	TL	E4	28.00/3.5	62.5	207B	17500/475 (ETRTO)		890	2075
	★★	TL	L4	28.00/3.5	62.5	224A2		28000/650	890	2075
	★★★★	TL	E4	28.00/3.5	62.5	225A2	29000/800	890	2075	



RR-212 (E4)



**Rigid
Dumpers**

★ Deep tread designed for severe and rocky surfaces.

- ★ Used for underground mining, open pits and quarries.
- ★ Specially designed sidewall provides extended protection from cutting.
- ★ Excellent combination of traction, stability and comfortable ride.

SIZE	STAR LEVEL	TYPE	CODE	STD RIM	TREAD DEPTH (MM)	LOAD INDEX	LOAD&PRESSURE (KG/KPA)		DIMENSION (MM)	
							50KM/H		SW	OD
18.00R33	★★	TL	E4	13.00/2.5	49	191B	10900/700		500	1875
	★★★	TL	E4	13.00/2.5	49	196B	12500/900		500	1875
21.00R35	★★	TL	E4	15.00/3.0	53	201B	14500/700		555	2040
24.00R35	★★	TL	E4	17.00/3.5	58	209B	18500/700		655	2175
	★★★	TL	E4	17.00/3.5	58	214B	21200/900		655	2175

(E4) RR-213



Rigid Dumpers



★ Deeper tread depth design with super cut resistance and wear resistance.

★ Larger pattern block with high pattern saturation to ensure longer tread life.

★ With excellent self-cleaning performance and anti-skidding performance of muddy, soft and slippery road conditions, enhance the tire traffic ability and operating stability.

SIZE	STAR LEVEL	TYPE	CODE	STD RIM	TREAD DEPTH (MM)	LOAD INDEX	LOAD&PRESSURE (KG/KPA)		DIMENSION (MM)	
							50KM/H	10KM/H	SW	OD
14.00R24	★★★	TT/TL	E4	10.00W	40	170B	6050/800	10000/1000	375	1368
14.00R25	★★★	TT/TL	E4	10.00/1.5 10.00/2.0	40	170B	6050/800	10000/1000	375	1368
16.00R25	★★★	TT/TL	E3	11.25/2.0	27	182B/196A2	8500/900	12500/1000	432	1493
	★★★	TT/TL	E4	11.25/2.0	43	182B/196A2	8500/900	12500/1000	432	1548



RR-214 (E4)



Rigid
Dumpers

★ High self-cleaning performance.

★ Extra sidewall protection and tear resistant compound provide anti-punching performance.

SIZE	STAR LEVEL	TYPE	CODE	STD RIM	TREAD DEPTH (MM)	LI/SS	DIMENSION (MM)		QTY/400T
							SW	OD	
27.00R49	★★	TL	E4	19.50/4.0	72.0	240A2/215B	735	2700	12
33.00R51	★★	TL	E4	24.00/5.0	82.0	253A2/235B	895	3060	8
37.00R57	★★	TL	E4	27.00/6.0	86.0	261A2/246B	1015	3440	6
40.00R57	★★	TL	E4	29.00/6.0	86.0	268A2/250B	1095	3595	6
46/90R57	★★	TL	E4	32.00/6.0	96.0	269A2/252B	1170	3595	6

(E4) RR-215



Rigid Dumpers



★ Deep tread and large pattern provide better grip and stability.

★ The tread rubber with low heat generation design effectively increases TKPH/TMPH.

★ Unique tread compound lead to lower wear rate and safer in driving.

SIZE	STAR LEVEL	TYPE	CODE	STD RIM	TREAD DEPTH (MM)	LI/SS	DIMENSION (MM)		QTY/400T
							SW	OD	
33.00R51	★★	TL	E4	24.00/5.0	90.0	235B	920	3030	8
40.00R57	★★	TL	E4	29.00/6.0	96.0	250B	1097	3560	6



RR-755 (E4)



Rigid Dumpers

★ With excellent traction and self cleaning performance.

★ Special pattern design, with elegant formal expressions.

★ Outstanding stability and operating comfort, with large pattern plate and long service life.

SIZE	STAR LEVEL	TYPE	CODE	STD RIM	TREAD DEPTH (MM)	LOAD INDEX	LOAD&PRESSURE (KG/KPA)		DIMENSION (MM)	
							50KM/H	10KM/H	SW	OD
14.00R24	★★★★	TT/TL	E4	10.00W	36	170B	6050/800		375	1418
14.00R25	★★★★	TL	E4	10.00/2.0	36	170B	6050/800		375	1418
16.00R25	★★★★	TT/TL	E4	11.25/2.0	43	182B/196A2	8500/900	12500/1000	432	1548

(L5) RR-113



- ★ Superior sidewall cut resistance.
- ★ Enhanced stability and riding comfort.
- ★ Long tread life. ★ Exceptional casing durability.
- ★ Extra deep tread pattern specially designed for loaders and dozers on extremely rocky surfaces in open pit, quarries and underground mines.

SIZE	STAR LEVEL	TYPE	CODE	STD RIM	TREAD DEPTH (MM)	LOAD INDEX	LOAD&PRESSURE (KG/KPA)		DIMENSION (MM)	
							50KM/H	10KM/H	SW	OD
17.5R25	★★★	TL	L5	14.00/1.5	64	193A2		11500/750	445	1399
20.5R25	★★	TL	L5	17.00/2.0	68	193A2		11500/650	521	1548
23.5R25	★★	TL	L5	19.5/2.5	78	201A2	14500/600(GB)		597	1673
26.5R25	★★	TL	L5	22.00/3.0	88	209A2		18500/650	673	1798
29.5R25	★★	TL	L5	25.00/3.5	95	216A2		22400/650	749	1921
35/65R33	★★	TL	L5	28.00/3.5	95	223A2		27250/650 (ETRT)	890	2075



RR-116 (L5S)



Underground
Shuttle Trucks



Loader

★ Smooth, extra deep tread pattern is specially designed for loaders, scrapers and other engineering machines which work underground mine alley, tunnels or other harsh conditons.

★ Special cut resistant tread compound and formula and smooth, extra thick tread offers good performance, wear resistance and puncture resistance against ores and coal.

SIZE	STAR LEVEL	TYPE	CODE	STD RIM	TREAD DEPTH (MM)	LOAD INDEX	LOAD&PRESSURE (KG/KPA)	DIMENSION (MM)	
							10KM/H	SW	OD
12.00R24	★★★	TT/TL	L5S	8.5	56	177A2	7300/950	315	1275
14.00R24	★★★	TT/TL	L5S	10.00W	56	188A2	10000/950	375	1418
17.5R25	★★	TT/TL	L5S	14.00/1.5	60	182A2	8500/650	445	1399
18.00R25	★★	TL	L5S	13.00/2.5	83	204A2	16000/825	498	1673
23.5R25	★★	TL	L5S	19.50/2.5	70	201A2	14500/650	597	1617
26.5R25	★★	TL	L5S	22.00/3.0	85	209A2	18500/650	673	1798
29.5R25	★★	TL	L5S	22.00/3.0	90	216A2	22400/650	749	1921
29.5R29	★★	TL	L5S	25.00/3.5	90	218A2	23600/650	749	2023

(IND) RR-888



★ Unique dentate pattern design in tire shoulder provides good mud and sand handling ability.

★ The tread pattern design improves tire traction ability and turning control with excellent maneuverability when vehicles plunge in mires.

SIZE	PR	TYPE	STD RIM	TREAD DEPTH (MM)	LOAD INDEX	LOAD&PRESSURE (KG/KPA)		DIMENSION (MM)	
						SINGLE	DUAL	SW	OD
14.00R20	20	TT/TL	10.00	20	164/161F	5000/790	4625/790	375	1240



RR-555 (IND4, IND5)



★ Suitable for straddle carriers, forklifts and other port equipment.

★ Special tire construction design has ultra-deep tread, excellent carrying capacity and long service life.

SIZE	STAR LEVEL	TYPE	CODE	STD RIM	TREAD DEPTH (MM)	LOAD INDEX	LOAD&PRESSURE (KG/KPA)	DIMENSION (MM)	
							25KM/H	SW	OD
12.00R24	★★★	TT/TL	IND5	8.5	40	180A5	7500/1000	315	1275
14.00R24 (385/95R24)	★★★	TT/TL	IND5	10.00W	60	196A5	12500/1000	375	1415
18.00R25 (505/95R25)	★★★	TL	IND4	13.00/2.5	63.5	214A5	21200/1000	498	1673

(IND) RR-711



- ★ Special pattern design which has good performance in puncture resistance.
- ★ With good traction and grip performance.
- ★ Specially designed for mine dump truck, with excellent resistance to cutting.

SIZE	PR	TYPE	STD RIM	TREAD DEPTH (MM)	LOAD INDEX	LOAD&PRESSURE (KG/KPA)		DIMENSION (MM)	
						SINGLE	DUAL	SW	OD
14.00R20	20	TT/TL	10.00	21	164/161F	5000/790	4625/790	375	1240



RR-712 (IND)



★ Mainly for drive wheels.

- ★ Applicable for driving on bad road conditions, especially for mining road.
- ★ Widen and deeper pattern design with excellent grip, traction and ride ability performance.
- ★ The pattern is with good performance in cutting resistance, anti-puncture and anti-cracking.

SIZE	PR	TYPE	STD RIM	TREAD DEPTH (MM)	LOAD INDEX	LOAD&PRESSURE (KG/KPA)		DIMENSION (MM)	
						SINGLE	DUAL	SW	OD
11.00R20	22	TT	8.0	32	160/156B	4500/930	4000/930	293	1085
12.00R20	22	TT	8.5	32	162/158B	4750/930	4250/930	315	1125

(IND) RR-713



★ Suitable for mines, uneven bad road conditions.

★ Large block design with solid blocks and reinforced ribs connected to each other to provide with excellent comprehensive performance.

★ Wide and deep transverse pattern design with strong traction & grip and with longer life.

SIZE	PR	TYPE	STD RIM	TREAD DEPTH (MM)	LOAD INDEX	LOAD&PRESSURE (KG/KPA)		DIMENSION (MM)	
						SINGLE	DUAL	SW	OD
12.00R20	22	TT	8.5	28	162/158B	4750/930	4250/930	315	1125



RR-999 (MILITARY)



- ★ Unique block pattern design.
- ★ Better traction performance and self-cleaning performance.

- ★ Suitable for desert, Gobi, mud and other conditions, also suitable for driving on paved road.
- ★ Excellent load capacity and long service life.
- ★ Deep tread designed for severe and rocky surfaces.

SIZE	PR	TYPE	STD RIM	TREAD DEPTH (MM)	LOAD INDEX	LOAD&PRESSURE (KG/KPA)		DIMENSION (MM)	
						SINGLE	DUAL	SW	OD
14.00R20	20	TT/TL	10.00	20	164/161F	5000/790	4625/790	375	1240
16.00R20	22	TT/TL	11.25/2.0	20	174/171G	6700/760	6150/760	438	1309